



CERTIFICATE NUMBER
16-HG1476876-PDA-DUP

DATE
22 Jan 2016

ABS TECHNICAL OFFICE
Hamburg Engineering Department

CERTIFICATE OF DESIGN ASSESSMENT

This is to certify that a representative of this Bureau did, at the request of
KFG LEVEL AG

assess design plans and data for the below listed product. This assessment is a representation by the Bureau as to the degree of compliance the design exhibits with applicable sections of the Rules. This assessment does not waive unit certification or classification procedures required by ABS Rules for products to be installed in ABS classed vessels or facilities. This certificate, by itself, does not reflect that the product is Type Approved. The scope and limitations of this assessment are detailed on the pages attached to this certificate.

Product: **Level Indicator, By Pass Type**

Model: **AL..., AV..., ALD..., AVD..., AP..., ABA..., AS..., K..., WG..., GU...**

This Product Design Assessment (PDA) Certificate 16-HG1476876-PDA-DUP, dated 22/Jan/2016 remains valid until 21/Jan/2021 or until the Rules or specifications used in the assessment are revised (whichever occurs first).

This PDA is intended for a product to be installed on an ABS classed vessel, MODU or facility which is in existence or under contract for construction on the date of the ABS Rules or specifications used to evaluate the Product.

Use of the Product on an ABS classed vessel, MODU or facility which is contracted after the validity date of the ABS Rules and specifications used to evaluate the Product, will require re-evaluation of the PDA.

Use of the Product for non ABS classed vessels, MODUs or facilities is to be to an agreement between the manufacturer and intended client.

AMERICAN BUREAU OF SHIPPING



Ulf Numirski
Engineer/Consultant

NOTE: This certificate evidences compliance with one or more of the Rules, Guides, standards or other criteria of ABS or a statutory, industrial or manufacturer's standards. It is issued solely for the use of ABS, its committees, its clients or other authorized entities. Any significant changes to the aforementioned product without approval from ABS will result in this certificate becoming null and void. This certificate is governed by the terms and conditions as contained in ABS Rules 1-1-A3/5.9 Terms and Conditions of the Request for Product Type Approval and Agreement (2010).

KFG LEVEL AG

RUESSENSTR. 4

CH 6340 BAAR

Switzerland

Telephone: +41 (0)41 766 62 82

Fax: +41 (0)41 766 62 83

Email: info@kfg-level.com

Web: www.kfg-level.com

Tier: 2 - PDA Issued

Product: Level Indicator, By Pass Type**Model:** AL..., AV..., ALD..., AVD..., AP..., ABA..., AS..., K..., WG..., GU...**Intended Service:**

Liquid level gauging.

Description:

Float operated level sensors with magnetic transmission in a three wire potentiometer circuit.

Certified safe types: II 1/2G Ex c ia IIC T6 to T4 Ga/Gb, II 1/2G Ex c d ia IIC T6 to T4 Ga/Gb, II 1/2G Ex c d ib IIC T6 to T5 Gb, II 2 G Ex c ib IIC T6 to T5 Gb, II 2 G Ex c d IIC T6 to T4 Gb, II 1/2G Ex c ia IIC T6 to T3 Ga/Gb, II 1/2G Ex c d ia IIC T6 to T4 Ga/Gb, II 2D Ex c tb IIIC T80°C to T190°C/ T125°C Db IP6X, II 2G Ex c ib IIC T6 to T5 Gb, II 2G Ex c d IIC T6 to T4 Gb, II 2D Ex c tb IIIC T80°C to T95°C/ T140°C Db IP6X (SEV 11 ATEX 0187)
(For more details please see attachment)

Rating:

150 V AC/ 0.5 A/ 10 VA, 230 V AC/ 1 A/ 100 VA

Max. Working Pressure: 175 bar.

Max. Working Temperature: 200 deg C.

Degree of Protection: IP65.

Service Restriction:

Unit Certification is not required for this product. If the manufacturer or purchaser's request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined.

ATEX certified equipment is not to be installed in hazardous areas on U.S. vessels unless it can be proven to have been tested to the applicable IEC 60079 series standards by an independent laboratory accepted by the U.S. Coast Guard.

Comments:

Each particular installation is to be approved in conjunction with the relevant system, tank arrangement and hazardous zone.

The Manufacturer has provided a declaration about the control of, or the lack of Asbestos in this product.

Notes/Drawing/Documentation:

Drawing No. 1001 DOK_6044, Dimension Drawing, Revision: -, Pages: 1

Drawing No. 1001 Zchn1002_017, Dimension Drawing, Revision: -, Pages: 1

Drawing No. 1001 Zchn1002_018, Dimension Drawing, Revision: -, Pages: 1

Drawing No. 1001 Zchn1002_019, Dimension Drawing, Revision: -, Pages: 1

Drawing No. 1001_150, Catalog, Revision: -, Pages: 1

Drawing No. SEV_11 ATEX 0187, ATEX Certificate, Revision: -, Pages: 1

Terms of Validity:

This Product Design Assessment (PDA) Certificate 16-HG1476876-PDA-DUP, dated 22/Jan/2016 remains valid until 21/Jan/2021 or until the Rules or specifications used in the assessment are revised (whichever occurs first).

This PDA is intended for a product to be installed on an ABS classed vessel, MODU or facility which is in existence or under contract for construction on the date of the ABS Rules or specifications used to evaluate the Product.

Use of the Product on an ABS classed vessel, MODU or facility which is contracted after the validity date of the ABS Rules and specifications used to evaluate the Product, will require re-evaluation of the PDA.

KFG LEVEL AG

RUESSENSTR. 4

CH 6340 BAAR

Switzerland

Telephone: +41 (0)41 766 62 82

Fax: +41 (0)41 766 62 83

Email: info@kfg-level.com

Web: www.kfg-level.com

Tier: 2 - PDA Issued

Use of the Product for non ABS classed vessels, MODUs or facilities is to be to an agreement between the manufacturer and intended client.

STANDARDS

ABS Rules:

2016 Steel Vessel Rules, 1-1-4/7.7, 1-1-Appendix 3 and 4, 4-6-2/ 9.11.3, 4-6-4/ 13.5.6(b)/ 15.3.4(b), 4-8-3/ 1.7/ 1.11.1/ 1.17/ 13, 4-9-8/ 7/ 13

National:

NA

International:

NA

Government:

NA

EUMED:

NA

OTHERS:

NA